

# 7" Monitor 3 Camera Inputs Single Camera View 710310

Dimensions: (w/o mount) 7.3"W x 4.9"H x 2"D

Screen Ratio: 16:10

Weight: 395g

Operating Voltage: DC8-28 Volts

Operating Temperature: -15°F to 160°F

Display Resolution: 2400 (3) x 480/800 x 480

Video Signal System: PAL/NTSC (Automatic)

OSD Menu Function: Brightness, Contrast, Camera Input Plus Separately  
Set Each Camera's Trigger Priority,

Image Switch Delay Time 1-30 Seconds, Mirror/Normal Image Select

Input Signal: Composite 1.0Vpp

Brightness: 350 cd/m<sup>2</sup> (Auto Dimming at Night)

Contrast Ratio: 500:1



# MiniBox Camera w/ Heater 2.9mm Lens 710311



- Hi-Res Color Series
- Day/Night Viewing
- Intelligent IR Technology for Eliminating IR Hot Spots
- Adjustable Viewing Angle
- Built-In Heater
- Waterproof
- 
- Image Type: 1/3" Sony Color CCD
- Resolution: 600
- Night Vision Range: 0 Lux w/ Infrared Lighting, 45'
- Shockproof Rating: 20G
- Video Output: 1.0Vpp-75 OHMS
- Operating Temperature: -15°F to 160°F
- Operating Voltage: DC12V (Regulated Power Provided From Monitor)
- Dimensions: (w/o Mount) 3"W x 2.8"H x 2.7"D
- Weight: 360g
- Current: 200mA, 400mA w/ Heater On